



IPPMC-7140

**700TVL High Res, 1/3" SONY Super HAD CCD II,
3.7mm fixed, WDR D&N Mini Pinhole Camera**

FEATURES

- 1/3" SONY Super HAD CCD II sensor
- 700 TVL High Resolution
- Effective Pixels : 976 (H) x 582 (V)
- Minimum Illumination is 0.00006 Lux @ (F2.5, AGC ON)
- 75dB WDR (Wide Dynamic Range)
- Electronic Day & Night
- Fixed Lens 3.7mm (Optional 2.8mm), Angle of View : 70°
- 3D DNR (3D Digital Noise Reduction) , BLC, AWB
- Privacy Masking, Motion Detection
- Supported Video Compressions : MJPEG / H.264
- OSD Menu
- Comes with Mini mounting bracket
- DC12V Power Supply

SPECIFICATIONS

Camera Model	IPPMC-7140
Features	
Image Sensor	1/3" SONY Super HAD CCD II
TV-Lines (E.Pixels)	700 TVL (976px x 582px)
Min. Illumination	0.00006 Lux @ (F2.5, AGC ON, sensitivity x 512)
Shutter time	1/50s ~ 1/100,000s
Lens	3.7mm @ F2.5 (2.8mm optional)
Angle of View	70° (Horizontal)
Lens Mount	M12
Wide Dynamic Range	75dB WDR
DNR	3D DNR
Day and Night	Electronic
S/N Ratio	>= 62dB
Video Compression	H.264 / MJPEG
Video Output	1Vp-p composite output (75 Ω/BNC)
Functions	AGC, BLC, AWB, Anti-Flicker.

Camera Model	IPPMC-7140
Features (Continued)	
Functions	3DNR, Sharpness, Brightness, Saturation, Eclipse, Resolution, Electronic image stabilization, Digital Zoom, Mirror, Defect Pixel Correction. Motion detection, privacy masking.
Environmental	
Operating Temperature	-30°C ~ 60°C (-22°F ~ 140°F)
Electrical	
Input Voltage	DC12V ± 10%
Power Consumption	Max. 2W
Physical	
Dimensions	32(W) x 32(H) x 30(D) mm
Weight	310 g (0.68 lbs)
Regulatory Certifications	
	FCC, CE, C-TICK, UL

MADE IN KOREA